



RECOMMEND P.C.B LAYOUT THICKNESS=DIM 'C' mm
 (COMPONENT SIDE) TOLERANCE±0.05mm

NOTES:

- MATERIAL:
 HOUSING: HIGH TEMPERATURE THERMAL PLASTIC BLACK. UL94 H-B HALOGEN FREE.
 CONTACT: COPPER ALLOY
 SHELL:SUS
 FINISH:
 CONTACT: UNDER-PLATING: 50µ" MIN. NICKEL OVERALL
 CONTACT AREA PLATING: 2µ" MIN. GOLD PLATED OVER 30µ" Ni-Pd
 SOLDER TAIL PLATING: 100µ" MIN. TIN PLATING
 SHELL: 30µ" MIN. NICKEL PLATED OVERALL
- PART NO. DESCRIPTION:

UD X CXX10 X - X X - X X-X
 SHELL PLATED
 N: NICKEL PLATED
 TYPE
 CONTACT PLATED
 N: 2µ"Au+30µ"Ni-Pd
 HOUSING MATERIAL
 A: PA9T(L/F)
 REV A
 1: CONFORM TO SONY GP
 0: NO MARK
 PACKAGE
 2: TYPE REEL
 HOUSING COLOR
 Y:BLUE (300C).

TABLE:

PART NO.	DIM A	DIM B	DIM C
UDXC1510N-AY-XX-X	1.8	1.8	1.6
UDXC1310N-AY-XX-X	1.2	1.2	1.0

